



TRANE®

CONQUEST

**Air-Cooled Scroll Chillers
and Heat Pumps**

CGAX/CXAX 40-165 kW

Conquering Customers' Hearts



Trane Conquest

Conquering Customers' Hearts

Your primary concern when selecting HVAC equipment for your building should be comfort, efficiency and economy. Trane Conquest chillers and heat pumps uniquely combine the best in performance with the best in value.

The smart and versatile Conquest range has been designed by Trane using over 100 years of experience to provide optimized efficiency with exceptionally low sound levels and high quality of materials and construction for total reliability.



CONQUEST

Efficient, quiet, dependable and smart



Energy Efficient

The better the efficiency, the lower your energy costs. Trane has developed the Conquest range to optimize your Total Cost of Ownership (TCO). The design of the units has been optimized for part load operation since units always modulate throughout their real life utilization.



Quiet

Operating noise can be a significant intrusion into a sensitive building environment. The Conquest range includes both standard and low sound level models, so you can choose what suits your particular application. No compromise in operational efficiency has been made in providing these levels of sound attenuation. The Low Noise (LN) model achieves an impressive 47 dB(A) sound pressure level (@10m in free field).



Reliable

With equipment as critical as an HVAC system, quality is non-negotiable. At Trane we manufacture and design the core components and put our systems through extremely demanding performance and reliability tests. As a result, you have peace of mind, and we have the confidence to offer exceptional warranty cover of up to ten years.



Smart

The Trane Conquest range is made smart to make your life easier. It has the capability to provide all-year cooling in ambients from -18°C up to 46°C and all-year heating down to -15°C. It is ideally suited to comfort applications and is fully Ecodesign 2015 and 2017 compliant (heating mode as cooling target are not defined yet).

Units have a compact and low height design for quick and easy integration into jobsites. Footprint has been reduced by 30% versus the previous generation and unit height is between 1.5 and 1.75m depending on the model and options.

Operation could not be easier thanks to the new Trane light commercial controller, the LCD interface and the optional Deluxe Display featuring a user-friendly 7" touchscreen. Connectivity with Modbus, BACnet®, LonTalk® and Trane BMS is made simple with the Smart Com interface. Remote control via smart phone or tablet means you can monitor and manage your system round the clock, regardless of location.



Trane proprietary technology*

provides the innovative solution your building needs

* Electronically Commuted (EC) fans

- Improved capacity modulation
- Enables low ambient operation
- Reduced power consumption
- Reduced energy costs

Adaptive Frequency Drive

- Optional on water pumps
- Improves user comfort and process accuracy
- Reduces pump consumption and energy bills



* New Trane light commercial controller

- LCD display with clear messages in 15 languages
- Easy use with navigation buttons
- Clear display of critical information
- Customer communication package

Optional deluxe 7" color touchscreen display:

- Monitor data trending, clear alarms logging
- TIS enable for remote monitoring



Optional hydraulic module

- Housed within the chiller frame to keep overall size to a minimum
- Single or dual pump
- Optional water buffer tank



* Connectivity



- Smart Com interface integrates seamlessly with LonTalk®, BACnet®, Modbus and Trane BMS

* Micro-channel condenser coils

- Leading edge coil design for increased corrosion resistance
- Longer life expectancy
- Increased efficiency with less refrigerant
- Reduced carbon footprint
- 4 times lower unit weight

* Full remote control

- Web-enabled interface for full visibility
- Connect to smart phones, tablets or workstations
- Full remote monitoring and control of your system with TIS enable

Scroll compressors

- Direct drive, low speed
- Few moving parts, providing high efficiency, reliable operation and simplified maintenance

The Total Package

Quality, performance and reliability

The Trane advantage

Trane is recognized as a world leader with over 100 years of experience in creating and sustaining safe, comfortable and energy efficient environments while improving the performance of buildings around the world.

Trane solutions optimize indoor environments with a broad portfolio of energy efficient heating, ventilating and air conditioning systems, building services, parts support and advanced controls.

To ensure your equipment continues working at its optimum throughout the life of the building, Trane provides a full range of service solutions combined with in-house expertise and an extensive support network.

Smart controls

Choose from two unit controller options. Both offer total control over your system to optimize performance and reliability.

New Trane light commercial controller

- LCD display with 6 navigation buttons
- Easy to understand messages in a choice of 15 languages
- Electronic expansion valves (EXV) for superior control
- Customizable with customer communication package
 - Chilled water set-point
 - Demand limit
 - Analogue capacity output
 - Programmable relays

Optional Deluxe Display

- 7 "color touchscreen
- Easy to use, intuitive menus
- Clear alarm log
- Full data trending
- TIS enable for remote monitoring



General Specifications

CGAX Standard Efficiency

Eurovent performances (1)		CGAX 015 SE	CGAX 017 SE	CGAX 020 SE	CGAX 023 SE	CGAX 026 SE	CGAX 030 SE	CGAX 036 SE	CGAX 039 SE	CGAX 045 SE	CGAX 035 SE	CGAX 040 SE	CGAX 046 SE	CGAX 052 SE	CGAX 060 SE
Net cooling capacity	(kW)	43	50	60	66	76	84	97	110	126	98	117	130	146	164
EER		2.95	2.85	3.14	3.01	2.96	2.90	2.93	2.92	2.99	2.85	3.00	2.85	2.74	2.86
ESEER		3.96	4.01	3.90	3.90	4.04	3.96	4.05	4.28	4.00	3.95	3.66	3.67	3.76	3.88
Eurovent efficiency class - cooling		B	C	A	B	B	B	B	B	C	B	C	C	C	B
Sound power level (Standard Noise)	(dBA)	83	83	85	85	85	86	84	85	87	86	88	88	88	89
Sound power level (Low Noise)	(dBA)	77	77	79	79	79	80	79	80	82	81	82	82	82	83
Refrigerant circuit															
Number of circuit(s)		1	1	1	1	1	1	1	1	1	2	2	2	2	2
Number of compressors per circuit		2	2	2	2	2	2	3	3	3	2	2	2	2	2
Dimensions															
Unit length	(mm)	2346	2346	2346	2346	2346	2346	2327	2327	2327	2327	2327	2327	2327	2327
Unit width	(mm)	1285	1285	1285	1285	1285	1285	2250	2250	2250	2250	2250	2250	2250	2250
Unit height (Standard Noise)	(mm)	1524	1524	1524	1524	1524	1524	1524	1524	1524	1524	1524	1524	1524	1524
Unit height (Low Noise)	(mm)	1747	1747	1747	1747	1747	1747	1747	1747	1747	1747	1747	1747	1747	1747
Weights (2)															
Operating weight	(kg)	497	509	552	557	587	599	819	824	879	887	973	983	1004	1029

CXAX Standard Efficiency

Eurovent performances (1)		CGAX 015 SE	CGAX 017 SE	CGAX 020 SE	CGAX 023 SE	CGAX 026 SE	CGAX 030 SE	CGAX 036 SE	CGAX 039 SE	CGAX 045 SE	CGAX 035 SE	CGAX 040 SE	CGAX 046 SE	CGAX 052 SE	CGAX 060 SE
Net heating capacity	(kW)	40	47	53	63	68	78	95	110	120	95	107	126	139	156
COP		2.88	2.95	3.12	3.03	2.96	3.03	3.13	3.11	3.06	3.08	3.11	3.00	3.00	3.00
SCOP		124%	126%	139%	128%	125%	130%	132%	129%	129%	131%	137%	125%	129%	129%
Eurovent efficiency class - heating		C	C	B	B	C	B	B	B	B	B	B	B	B	B
Net cooling capacity	(kW)	43	49	58	67	74	82	96	109	121	98	111	131	145	161
EER		3.01	2.93	2.93	3.03	2.90	2.89	2.99	3.06	2.87	2.96	2.86	3.03	2.91	2.85
ESEER		4.14	4.14	4.28	4.09	4.04	4.00	4.37	4.34	4.13	4.12	4.21	3.96	4.03	3.98
Eurovent efficiency class - cooling		B	B	B	B	B	C	B	B	C	B	C	B	B	C
Sound power level (Standard Noise)	(dBA)	84	84	84	85	85	86	86	87	88	87	87	88	88	89
Sound power level (Low Noise)	(dBA)	78	78	78	80	80	81	80	81	82	81	81	83	83	84
Refrigerant circuit															
Number of circuit(s)		1	1	1	1	1	1	1	1	1	2	2	2	2	2
Number of compressors per circuit		2	2	2	2	2	2	3	3	3	2	2	2	2	2
Dimensions															
Unit length	(mm)	2346	2346	2346	2346	2346	2346	2327	2327	2327	2327	2327	2327	2327	2327
Unit width	(mm)	1285	1285	1285	1285	1285	1285	2250	2250	2250	2250	2250	2250	2250	2250
Unit height (Standard Noise)	(mm)	1524	1524	1524	1524	1524	1724	1524	1524	1524	1524	1524	1524	1524	1724
Unit height (Low Noise)	(mm)	1747	1747	1747	1747	1747	1947	1747	1747	1747	1747	1747	1747	1747	1947
Weights (2)															
Operating weight	(kg)	539	545	582	624	630	665	881	925	942	974	998	1072	1093	1163

(1) Cooling at evaporator water temperature: 12°C / 7°C, condenser air temperature 35°C according to EN14511:2013

Heating at evaporator water temperature: 40°C/45°C, condenser air DB/WB 7°C/6°C, according to EN14511:2013

(2) Rated condition without pump package

Range Description

a model for every application

The Trane Conquest range

- Thirteen unit sizes providing capacities from 40 kW to 165 kW
- Cooling only CGAX: ambient from -18°C to $+46^{\circ}\text{C}$, leaving water temperature down to -12°C
- Heat pump CXAX: ambient down to -15°C , leaving water temperature up to 60°C
- Two acoustic versions: Standard Noise (SN), Low Noise (LN)
- Single or dual circuit choice on 90-130 kW range

Standard options

- Hydraulic module
- Buffer tank
- Variable Primary Flow
- Low ambient down to -18°C
- Partial heat recovery
- Modbus, BACnet®, LonTalk® communication interfaces



Trane® is a brand of Ingersoll Rand®. Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Ingersoll Rand®, Trane®, Thermo King® and Club Car® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a global business committed to a world of sustainable progress and enduring results.



engineer.trane.com

trane.com

ingersollrand.com

Trane has a policy of continuous product and product data improvement and reserves the right to change design and specifications without notice. Trane bvba, Lenneke Marelaan 6, 1932 Sint-Stevens-Woluwe, Belgium, ON 0888.048.262 - RPR Brussels

We are committed to using environmentally conscious print practices that reduce waste.

© 2014 Trane – All rights reserved
CG-SLB025-E4 August 2014